



tecniwell

JET-GROUTING, GROUTING AND DRILLING EQUIPMENT



TW 400/S

HIGH PRESSURE TRIPLEX PUMP



Technical Features


Power input / puissance max / maximale Kraft	368 kW	500 HP	
Max pressure / pression maximale / maximaler Druck	80 MPa	800 bar	11600 psi
Max flow rate / débit maximale / maximale Durchflussrate	580 lt/min	153 gpm	
Piston diameter / diamètre du piston / Kolbendurchmesser	From 3" (76,2mm) to 5" (127mm)		
Stroke / Course / Hubweg	6" – 152,4		
Maximum stroke rate / coup par minute / max Hub pro Minute	130 / min	130 spm	
Suction diameter / diamètre d'aspiration / Saugdurchmesser	5"	127 mm	
Output diameter / diamètre de sortie / Ausgangsdurchmesser	1"1/2	38,1 mm	

Bareshaft dimensions and weight

Width 1450 mm - 4'9"	Height 1000 mm - 3'3"	Lenght 2050 mm - 6'8"	Weight 4300 Kg - 9480 lb
----------------------	-----------------------	-----------------------	--------------------------

Container dimensions and weight

Width 2438 mm - 7'12"	Lenght 6055 mm - 19'10"	Height 2591 mm - 8'6"	Weight 12000 Kg - 26460 lb
-----------------------	-------------------------	-----------------------	----------------------------



JET-GROUTING, GROUTING AND DRILLING EQUIPMENT

Via 1° Maggio, 61 – 29027 Podenzano (PC) – Italy – Tel. + 39 0523 524086
e-mail: info@tecniwell.com – www.tecniwell.it

All technical data are purely indicative and subject to change without notice